

Unit No. BBS-KA01

ULTRA HIGH PRESSURE HYDROJETTING UNIT



Frame, slings and shackles in acc. to
Machine directives

Dimension L x W x H mm	:	L 4505	W 2410	H 2820
Weight	:	6000		
Lifting/Transport	:	Forklift channels & lifting slings (OFFSHORE CONTAINER)		
Ref. cert./Ser no. Frame	:	BBS-KA01		

Water supply	:	Via suction booster pump with 2-7 bar water pressure		
Volume feed-water tank	:	225 l		
Volume diesel tank	:	257 l		
Flow rate	:	10 gpm		
M.A.W.P.	:	2800 bar		

Pump : NLB Model 40305DS
Dual rupture disc protecting against over-pressurization

Motor	:	Cummins Diesel engine, 6 Cyl., 305 hp Turbocharger w/ intercooler, Max. 2100 rpm		
Control panel	:	Oil-pressure, temperature, hour meter and RPM gauges		
Diesel shutdown if	:	<ul style="list-style-type: none">- High temperature- Low oil pressure- Low pressure in feed-water- Manual emergency shut-down		
Filter feed water	:	2 micron washable filter bag		
Equipment/Functions	:			
Other information	:	Dual gun cleaning operation		