

LUPROMAX[®]

Lubricates • Protects • Maximizes

LUPROMAX ENGINE OIL ADDITIVES SERIES

PRODUCT BROCHURE

Version Release 2007.7.1

NATO STOCK NO. 9150-32-078-8661



LUPROMAX LUBRICANT RANGE

- Metalworking Fluids
- Greases - Mineral, Silicone, Synthetic
- Gear Oil Additives
- Open Gear Lubricants
- Pulling Lubricants
- Engine Oil Additives
- Fuel Oil Additives
- Penetrating Oil Additives
- Wire rope Lubricants
- Aerosol Lubricants

PRODUCT MODEL

LUPROMAX

PRODUCT CATEROGY

LUPROMAX Engine Oil Additives Series

PRODUCT NAME

LUPROMAX -EA

PREMIUM QUALITY ENGINE OIL WITH METAL CONDITIONER ADDITIVE
MEETS U.S. MIL-I-46152B

PRODUCT BRIEF

LUPROMAX[®]-EA is a proprietary metal and engine oil conditioner. It was originally designed for use in gear boxes and crank cases.

However LUPROMAX[®]-EA concentrate demigrates numerous properties when mixed with lubrication fluids, making it a very versatile additive for numerous lubrication applications. It is a non-particulate, non-harmful environmentally friendly metal conditioner, thus, eliminating the fear of clogging your oil-filter.

Contact Us

Sujeng
 PT. Bumi Marga Kharisma Utama
 Cluster Paris Blok W3 No.5
 Balikpapan Baru, Balikpapan 76114
 East Kalimantan - Indonesia
 Telp. : (0542)-8879369
 Fax : (0542)-8879369
 Mobile : 0811590477
 Email : sujeng@bmku.co.id



LUPROMAX-EA
www.lupromax.com

FEATURES & BENEFITS

- Increases fuel mileage
- Decreases oil consumption
- Decreases smoking
- Stabilizes compression
- Neutralizes harmful crank case acids
- Extends engine life
- Maximizes engine power
- Combats engine wear
- Increases horsepower
- Restores compression
- Meets MIL-I-46152B
- Reduces Emission
- Fuel Saving up to 10% when LUPROMAX[®]-EA is used and directed
- Repairs by plating into minor scratches and surface imperfections

APPLICATIONS

LUPROMAX[®]-EA can be used in high compression performance cars, trucks, tractors, excavators, compressors, buses, gear boxes, crank cases and other industrial applications.

DIRECTIONS FOR USE

DOSAGE: 250 ml of LUPROMAX[®]-EA to 4 litres of Engine Oil.

TYPICAL PROPERTIES

APPEARANCE

- Viscous Liquid

FLASH POINT

- above 230°C

ODOUR

- Bland petroleum

COLOUR

- Amber

POUR POINT

- 9°C

SPECIFIC GRAVITY

- 1.019

pH

- 7

For more information about LUPROMAX, please request for LUPROMAX PRODUCT GUIDE from any LUPROMAX representative.

Please contact our distributor or reseller for more information:

Contact Us

Sujeng
PT. Bumi Marga Kharisma Utama
Cluster Paris Blok W3 No.5
Balikpapan Baru, Balikpapan 76114
East Kalimantan - Indonesia
Telp. : (0542)-8879369
Fax : (0542)-8879369
Mobile : 0811590477
Email : sujeng@bmku.co.id